

VINYLTECH SHIPPING DATA

VINYLTECH



PVC • PIPE

SIZE	O.D.	POUNDS/100'	FEET/LIFT	LIFTS/TRUCK	FEET/TRUCK
AWWA C900 DR 18 PRESSURE CLASS 235					
4	4.80	251.6	1020	16	16320
6	6.90	521.2	440	16	7040
8	9.05	903.0	200	20	4000
10	11.10	1364.4	240	12	2880
12	13.20	1935.8	60-80	28	1960
AWWA C900 DR 14 PRESSURE CLASS 305					
4	4.80	317.5	1020	16	16320
6	6.90	658.7	440	16	7040
8	9.05	1139.7	200	20	4000
10	11.10	1722.3	240	12	2880
12	13.20	2445.5	60-80	28	1960
AWWA C905 DR 25 PRESSURE RATED 165					
*14	15.30	1880.0	120	12	1440
16	17.40	2575.0	40-60	20	1000
18	19.50	3090.0	40/60	20	1000
*20	21.60	3790.0	80	8	640
*24	25.80	5420.0	60	6	360
AWWA C905 DR 18 PRESSURE RATED 235					
*14	15.30	2570.0	120	12	1440
16	17.40	3475.0	40-60	20	1000
18	19.50	4210.0	40/60	20	1000
*20	21.60	5180.0	80	8	640
*24	25.80	7410.0	60	6	360

SIZE	O.D.	POUNDS/100'	FEET/LIFT	LIFTS/TRUCK	FEET/TRUCK
ASTM D3034 SDR 35 PS 46 x 20'					
4	4.215	104.2	1680	12	20160
6	6.275	229.0	700	12	8400
8	8.400	410.3	400	12	4800
10	10.500	643.9	240	12	2880
12	12.500	922.7	80	28	2240
15	15.300	1361.0	120	12	1440
ASTM D3034 SDR 35 PS 46 x 14'					
4	4.215	105.7	1176	18	21168
6	6.275	232.6	490	18	8820
8	8.400	417.8	280	18	5040
10	10.500	657.4	168	18	3024
12	12.500	944.1	56	42	2352
15	15.300	1390.0	84	18	1512
ASTM F679 PS 46 x 14'/20'					
18 x 20'	18.071	2095.0	40-60	20	1000
18	18.071	2115.0	28-42	30	1050
*21	22.047	2850.0	56	12	672
*24	24.803	3630.0	56	12	672
ASTM D3034 SDR 26 PS 115 x 14'					
4	4.215	150.0	1176	18	21168
6	6.275	320.0	490	18	8820
8	8.400	580.0	280	18	5040
10	10.500	900.0	168	18	3024
12	12.500	1300.0	56	42	2352
15	15.300	1800.0	84	18	1512
ASTM F679 PS 115 x 14'					
18	18.071	2710.0	28-42	30	1050
*21	22.047	3800.0	56	12	672
*24	24.803	4840.0	56	12	672

*NORTHERN PIPE PRODUCTS

SHIPPING DATA