

| | SIZE | O.D. | POUNDS/100' | FEET/LIFT | LIFTS/TRUCK | FEET/TRUCK |
|--|------|-------|-------------|-----------|-------------|------------|
| AWWA C900 DR 18 PRESSURE CLASS 235 | 4 | 4.80 | 251.6 | 1020 | 16 | 16,320 |
| | 6 | 6.90 | 521.2 | 440 | 16 | 7,040 |
| | 8 | 9.05 | 903.0 | 200 | 20 | 4,000 |
| | 10 | 11.10 | 1364.4 | 240 | 12 | 2,880 |
| | 12 | 13.20 | 1935.8 | 60-80 | 28 | 1,960 |
| AWWA C900 DR 14 PRESSURE CLASS 305 | 4 | 4.80 | 317.5 | 1020 | 16 | 16,320 |
| | 6 | 6.90 | 658.7 | 440 | 16 | 7,040 |
| | 8 | 9.05 | 1139.7 | 200 | 20 | 4,000 |
| | 10 | 11.10 | 1722.3 | 240 | 12 | 2,880 |
| | 12 | 13.20 | 2445.5 | 60-80 | 28 | 1,960 |
| AWWA C900 DR 25 PRESSURE RATED 165 | 14 | 15.30 | 1880.0 | 120 | 12 | 1,440 |
| | 16 | 17.40 | 2575.0 | 40-60 | 20 | 1,000 |
| | 18 | 19.50 | 3090.0 | 40/60 | 20 | 1,000 |
| | *20 | 21.60 | 3790.0 | 80 | 8 | 640 |
| | *24 | 25.80 | 5420.0 | 60 | 6 | 360 |
| AWWA C900 DR 18 PRESSURE RATED 235 | 14 | 15.30 | 2570.0 | 120 | 12 | 1,440 |
| | 16 | 17.40 | 3475.0 | 40-60 | 20 | 1,000 |
| | 18 | 19.50 | 4210.0 | 40/60 | 20 | 1,000 |
| | *20 | 21.60 | 5180.0 | 80 | 8 | 640 |
| | *24 | 25.80 | 7410.0 | 60 | 6 | 360 |

| | SIZE | O.D. | POUNDS/100' | FEET/LIFT | LIFTS/TRUCK | FEET/TRUCK |
|--------------------------------------|----------|--------|-------------|-----------|-------------|------------|
| ASTM D3034 SDR 35 PS 46 x 20' | 4 | 4.215 | 104.2 | 1680 | 12 | 20,160 |
| | 6 | 6.275 | 229.0 | 700 | 12 | 8,400 |
| | 8 | 8.400 | 410.3 | 400 | 12 | 4,800 |
| | 10 | 10.500 | 643.9 | 240 | 12 | 2,880 |
| | 12 | 12.500 | 922.7 | 80 | 28 | 2,240 |
| | 15 | 15.300 | 1361.0 | 120 | 12 | 1,440 |
| ASTM D3034 SDR 35 PS 46 x 14' | 4 | 4.215 | 105.7 | 1176 | 18 | 21,168 |
| | 6 | 6.275 | 232.6 | 490 | 18 | 8,820 |
| | 8 | 8.400 | 417.8 | 280 | 18 | 5,040 |
| | 10 | 10.500 | 657.4 | 168 | 18 | 3,024 |
| | 12 | 12.500 | 944.1 | 56 | 42 | 2,352 |
| | 15 | 15.300 | 1390.0 | 84 | 18 | 1,512 |
| ASTM F679 PS 46 x 14'/20' | 18 x 20' | 18.071 | 2095.0 | 40-60 | 20 | 1,000 |
| | 18 | 18.071 | 2115.0 | 28-42 | 30 | 1,050 |
| | *21 | 22.047 | 2850.0 | 56 | 12 | 672 |
| | *24 | 24.803 | 3630.0 | 56 | 12 | 672 |
| ASTM D3034 SDR 26 PS 115 x 14' | 4 | 4.215 | 150.0 | 1176 | 18 | 21,168 |
| | 6 | 6.275 | 320.0 | 490 | 18 | 8,820 |
| | 8 | 8.400 | 580.0 | 280 | 18 | 5,040 |
| | 10 | 10.500 | 900.0 | 168 | 18 | 3,024 |
| | 12 | 12.500 | 1300.0 | 56 | 42 | 2,352 |
| | 15 | 15.300 | 1800.0 | 84 | 18 | 1,512 |
| ASTM F679 PS 115 x 14' | 18 | 18.071 | 2710.0 | 28-42 | 30 | 1,050 |
| | *21 | 22.047 | 3800.0 | 56 | 12 | 672 |
| | *24 | 24.803 | 4840.0 | 56 | 12 | 672 |